

Product

# PRIMER 0230

cod. 6360 M040

**SPECIFIC PRIMER FOR CONCRETE BASED ON MOISTURE CURING POLYURETHANE RESINS, SUITABLE FOR SINGLE PACK MOISTURE CURING POLYURETHANE SEALANTS AND LIQUID MEMBRANES.**

Features

Enhances adhesion of moisture curing polyurethane sealants and coatings on concrete.

Application

Primer ready for use not to be diluted.  
Apply the primer exclusively on concrete.  
PRIMER 0230 can be applied by roller and brush.  
After application waiting from 30 minutes to 2 hrs. is necessary in order for the solvent contained to evaporate. Then proceed with the application of the compatible systems coats as described on the Technical Data Sheets of the various products.

Technical data

<b>Color</b>	amber
<b>Specific weight at 20°C</b>	1 ± 0.01 Kg/l
<b>Viscosity at 20°C</b>	30 ± 10 mPa.s (Vel.100 – Gir.1)
<b>Solids</b>	46% in weight 40% in volume
<b>Theoretical consumption</b>	150 g/m <sup>2</sup>
<b>Adhesion to concrete ASTM D 4541</b>	> 3 mPa.s
<b>Period over coating of sealant at 22°C, 50% RH</b>	minimum 20 minutes maximum 60 minutes
<b>Storage</b>	If kept in the original sealed packs in a dry, protected place at temperatures of +5°C to +35°C, the product will keep for 12 months.

All data and prescription reported on the present data sheet are based on the best lab and practical experience and should anyhow be considered as indicative. Considering all different uses and the occurring of situations and conditions independent from MPM (substrate, climate conditions, technical management etc. Those who intend to use the product should verify whether it is suitable for the specific conditions in which it will be applied before starting. MPM's responsibility covers the quality and production standards referring to the above listed data only. Data should also be verified for latest available version of data sheets which could be surpassed by a new version. Data may change any time without notice from MPM.