

STARTEX FC

CONTINUOUS FILAMENT POLYPROPYLENE FIBER MESH FOR THE PRODUCTION OF WATERPROOF MEMBRANES THROUGH IMPREGNATION WITH FLUID-STATE ELASTOMERIC PRODUCTS.



CHARACTERISTICS

Uv resistant

High impregnation

APPLICATION FIELDS

- Reinforcement for waterproofing with elastomeric products as **STARFLEX C**.

TECHNICAL DATA

Colour		Grey
Dimensions		Rolls with a length of 100 meters and height of 1 meter
Weight	EN ISO 9864	80 g/m ²
Thickness	EN ISO 9863-1	0,6 mm
Tensile strength	EN ISO 10319	5 kN/m
Elongation	EN ISO 10319	longitudinal: 90% transversal: 60%
Punching resistance	EN ISO 12236	700 N

The data and instructions given in this sheet, based on the best practical and laboratory experiences, are to be considered in any case indicative. Considering the different conditions of use, and the intervention of factors independent of MPM (support, environmental conditions, technical laying direction, etc.) whoever intends to use it is required to establish whether or not the product is suitable for use. Our warranty obligation is limited to the quality and constancy of the finished product for the above data, only for technical sheets accompanied by stamp and countersignature by our delegated personnel. site. Furthermore, the customer is required to verify that these values are valid for their relevant batch of product and are not superseded and/or replaced by subsequent editions and/or new formulations. The data contained may vary at any time without prior notice by MPM.