

STARFLEX H-ZERO

ONE-COMPONENT ELASTIC POLYURETHANE-BASED MEMBRANE FOR THE WATERPROOFING OF ROOFS AND TERRACES, NO ADR AND NO IMO

BENEFITS



Seamless waterproofing and water and weather resistance



High **elasticity** and **crack-bridging** capabilities



Excellent adhesion on concrete, tiles, sheath, PVC and metal



Low environmental impact, and no danger to users and transport

BRUSH ROLLER AIRLESS SPRAYING

LAYING STEPS




Preparation of the substrate, cleaning and realization of the perimeter flaps.



MPM specific primer application for the existing substrate.



Application of a first coat of **STARFLEX H-ZERO** liquid membrane > 0.7 kg/sqm and application of STARTEX reinforcement, going over by the roller.



Application of a second coat of **STARFLEX H-ZERO** liquid membrane > 0.7 kg/sqm.



Application of a last coat of **STARFLEX H-ZERO** liquid membrane > 0.6 kg/sqm



Application of aliphatic polyurethane top coat of the **POLISTAR** line.

SYSTEM ACCESSORIES



SEALER

APPLICATION FIELDS



PRIMER



PRIMER 0130 R

Universal onecomponent rapid primer. Adhesion on any substrates: bituminous sheath, PVC, tiles, concrete, metal, etc.

FINISH

top coat



STARFLEX MONO TOPAliphatic polyurethane

STARMASTIC P95

One component polyurethane sealant

FABRICS



STARTEX NW

Non-woven fabric 60 gsm h 100 cm x 100 ml



STARTEX NW Details

Non-woven fabric 60 gsm h 20 cm x 100 ml



STARTEX GM

Fiberglass 220 gsm h 127 cm x 50 ml



STARTEX FC

Spunbond 80 gsm h 100 cm x 100 ml






For all applications, it is always recommended to use **Startex** reinforcements.

(2





STRIPS



STARTEX TAPE BTAdhesive butyl strip



STARTEX TAPE ET

Waterproof elastic strip



STARTEX CORNER IN

Elastic strip for internal corner



STARTEX CORNER OUT

Elastic strip for external corner

STARFLEX H-ZERO:

the ecological evolution of the STARFLEX line.

A liquid waterproofing agent that eliminates the risks related to storage, transport and use, ensuring the reliable and proven waterproofing performance typical of STARFLEX.

ROOFS AND TERRACES





MIXER SRL - Divisione MPM

HQ: Via E. De Amicis 53 20123 Milano (MI) OPS: Via Adda 15 20073 Opera (MI) TEL: +39 02 576 09116 • @mpm_srl info@mpmsrl.com • www.mpmsrl.com