

STARFLEX MONO

SINGLE-COMPONENT ELASTIC POLYURETHANE-BASED MEMBRANE FOR THE WATERPROOFING OF ROOFS AND TERRACES

BENEFITS



Seamless **waterproofing** and water and weather resistance



High **elasticity** and **crack-bridging** capabilities



Excellent adhesion on concrete, tiles, sheath, PVC and metal

BRUSH



Low environmental impact, thanks to reduced VOC emissions

ROLLER AIRLESS SPRAYING

■ INSTALLATION STEPS




Preparation of the substrate, cleaning and construction of the perimeter flaps.



MPM specific primer application for the existing substrate.



Application of a first coat of **STARFLEX MONO** liquid membrane > 0.7 kg/sqm and drafting of STARTEX fabric, going over it with an unloaded roller.



Application of a second coat of **STARFLEX MONO** liquid membrane > 0.7 kg/sqm.



Application of a last coat of **STARFLEX MONO** liquid membrane > 0.6 kg/sgm



Application of aliphatic polyurethane finish of the **POLISTAR** line.

SYSTEM ACCESSORIES



APPLICATION FIELDS



PRIMER

PRIMER 0130 R

Universal singlecomponent rapid primer. Adhesion on different substrates: bituminous sheath, PVC, tiles, concrete, metal, etc.

FINISH

finish



STARFLEX MONO TOP Aliphatic polyurethane

Single-component

FABRICS



STARTEX NW

Non-woven fabric 60 gsm h 100 cm x 100 ml



STARTEX NW Details Non-woven fabric

60 gsm h 20 cm x 100 ml



STARTEX GM

Fiberglass 220 gsm h 127 cm x 50 ml



STARTEX FC

continuous thread fabric 80 gsm h 100 cm x 100 ml

SEALER



STARMASTIC P95

polyurethane





Installation surface in concrete, sheath, PVC or other



MPM Specific primer



STARFLEX MONO liquid membrane

For all applications, it is always recommended to use **Startex** reinforcements.

STRIPS



STARTEX TAPE BT Adhesive butyl strip



STARTEX TAPE ET Waterproof elastic strip



STARTEX CORNER IN Elastic strip for internal corner



STARTEX CORNER OUT

Elastic strip for external corner **STARFLEX MONO** is an iconic product in the seamless waterproofing sector, synonymous with quality and reliability. Thanks to its advanced formulation and long experience in the market, it represents a safe and proven choice to protect structures from the action of water and atmospheric agents.

70 YEARS OF CERTIFIED EXCELLENCE



30-years certification



Etag 005

25-years certification



Compliance with the minimum environmental criteria



CF 1504 certificate



Asbestos

asbestos encapsulation certificate



Uni 14891

certified for under-tile



MIXER SRL - Divisione MPM

HQ: Via E. De Amicis 53 20123 Milano (MI) OPS: Via Adda 15 20073 Opera (MI) TEL: +39 02 576 09116 • @mpm_srl info@mpmsrl.com • www.mpmsrl.com