

# STARTEX TAPE ET

ROLL OF POLYPROPYLENE FABRIC REINFORCED WITH  
THERMOPLASTIC ELASTOMER FOR CORNERS AND EDGES



## FEATURES

Polypropylene fabric reinforced with thermoplastic elastomer.

Ideal for reinforcing the waterproofing layer at corners and edges.

Enhances the mechanical resistance of the waterproofing system at corners.

Suitable for use at corners and edges, applied before or after the liquid waterproofing resin to reinforce the waterproofing layer.

## APPLICATION FIELDS

It is used as reinforcement between the first and second layer of liquid waterproofing membrane. The main areas of application are:

- Flat roofs
- Car parks
- Balconies
- Terraces
- Flanges and details

## TECHNICAL DATA

<b>Color</b>		Grey
<b>Specific weight</b>	UNI EN 29073/1	364 g/m <sup>2</sup>
<b>Thickness</b>		0,7 mm ± 0,1
<b>Tensile strenght</b>	EN ISO 10319	≥ 1,67 kN/m transverse ≥ 8,00 kN/m longitudinal
<b>Elongation at break</b>		>70%

The data and specifications reported in this datasheet, based on the best practical and laboratory experience, are to be considered indicative in any case. Considering the various conditions of use and the influence of factors beyond MPM's control (substrate, environmental conditions, application method, etc.), anyone intending to use the product is responsible for determining whether it is suitable for the intended application. Our warranty obligation is limited to the quality and consistency of the finished product with respect to the data reported above, and only for datasheets bearing the stamp and countersignature of authorized personnel from our headquarters. Furthermore, the customer is responsible for verifying that such values are valid for the specific batch of product of interest and have not been superseded or replaced by subsequent editions and/or new formulations. The data contained herein may change at any time without prior notice from MPM.